



SCISSOR LIFT

MICRO SLIM ELECTRIC

Micro 26[®]

Electric Scissor Lift

- Compact Size Almost 2 ft. (60 cm) Shorter Than Other 26 ft. (7.6m) Lifts
- 36 in. (90 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Extended Duty Cycle, Smoother Control and Fewer Leak Points
- Spacious 2-Person Platform (Indoors)/ 1-Person Platform (Outdoors) with 500 lb. (227 kg) Capacity
- Fully Proportional Lift and Drive Controls



Work Over 30 Ft. High Indoors in Tight Work Areas
with Micro Footprint

Standard Features

Work Area

Roll Out Deck Extension with Incremental Locking Positions
Standard Full Height Swing Gate
Lanyard Attachments (2)

Performance

Direct Electric Drive
Fully Proportional Drive and Lift Controls
Up To 25% Gradeability

Power

240Ah Maintenance-Free Batteries
Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components in
Swing Out Trays
Parking Brake Release Switch for Towing

Safety

Lift Control Orientation Designed to Mitigate Entrapment
Dedicated Compartments Protect Electrical and Hydraulic Components
Emergency Shut-Off at Platform and Lower Controls
Non-Skid Metal Deck Construction
Descent Alarm
Drive Speed Interlock
Multi-Axis Tilt Sensor
Multiple Disk Brakes
Scissor Maintenance Lock
Automatic Parking Brakes
Automatic Pothole Protection

Other Features

Removable Upper Controls
Voltage-Compensating Fully
Automatic Battery Charger
Hour Meter
Machine Tie Downs
Non-Marking Tires
All-Motion Alarm
Fork Lift Pockets
Flashing Beacon

Optional Features

Leak Containment System® (LCS)
Patent #11,112,060
Proactive Platform Safety
System® (PPSS)
900W Inverter
Tool Tray
Cold Weather Package
Pipe Rack
Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 26®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC.
Leak Containment System® is Patent #11,112,060

97024 DTD 1021

Micro 26®	U.S.	Metric
Heights		
Indoor Working Height*	31 ft.*	9.6 m*
Outdoor Working Height*	24 ft.*	7.5 m*
Indoor Platform Height	25 ft.	7.6 m
Outdoor Platform Height	18 ft.	5.5 m
Stowed Height (Top Guardrail)	90.3 in.	2.3 m
Stowed Height (Rails Folded)	78.75 in.	2 m
Stowed Height (Platform Floor)	47 in.	1.2 m
Guardrail Height	43.5 in	1.1 m
Toeboard Height	6 in.	0.15 m
Ground Clearance (Stowed)	3 in.	7.62 cm
Dimensions		
Length-Stowed (Overall)	74 in.	1.88 m
Length-Stowed (Ladder Removed)	68 in	1.73 m
Chassis Width	31.9 in	.81 m
Platform Length (Extended)	103.5 in.	2.63 m
Platform Length (Retracted)	68 in.	1.73 m
Roll-Out Deck Length	35.5 in.	.9 m
Platform Width (Outside)	29.1 in.	.74 m
Wheelbase	55 in.	1.4 m
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
Speed		
Raise/Lower Speed	30/25 sec	
Drive Speed (Stowed)	2.5 mph	4 km/h
Drive Speed (Elevated)	.5 mph	.8 km/h
Performance		
Gradeability	25% 14 degrees	
Turning Radius (Inside)	6 in.	15 cm
Weight**	4190 lbs.	1900 kg
Power Source	240Ah Maintenance-Free Batteries	
Controls	Proportional	
Tires	12 in. x 5 in	30 cm x 12.5 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: